



PRICE LIST

Ref No. RRKL/LP/BCISI/05/22
w.e.f. 23rd May 2022

THE ONLY INDIAN
WIRE BRAND
TRUSTED BY

85+

COUNTRIES
GLOBALLY



RR KÄBEL
WIRES & CABLES

**AKALMAND BANO,
SAHI CHUNO.**

AKALMAND BANO, SAHI CHUNO.



BUILDING WIRES

RR KÄBEL
WIRES & CABLES

INDIA'S ONLY WIRE WITH
REACH • RoHS
CE • CPR Compliant



SUPEREX FR

FR PVC Insulated Single Core Cables



RR Kabel make single core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN Code: 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
0.75	24/0.2	1250	24
1.0	14/0.3	1705	20
1.5	22/0.3	2485	12
2.5	36/0.3	3968	12
4.0	56/0.3	5786	8
6.0	84/0.3	8619	4
10.0	140/0.3	15733	3
16.0	126/0.4	25269	2

UNILAY HR FR

HR FR PVC Insulated Single Core Cables



RR Kabel make single core unsheathed Multistrand Flexible High Conductivity plain annealed Copper, HR FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN Code: 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.0	37/0.19	1789	20
1.5	37/0.23	2597	12
2.5	61/0.23	4157	12
4.0	61/0.29	6344	8
6.0	91/0.29	9431	8

FLAMEX FR-LSH

FR-LSH PVC Insulated Single Core Cables



RR Kabel make single core unsheathed Multistrand High Conductivity plain annealed Copper, FR-LSH PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN Code: 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.0	14/0.3	1771	20
1.5	22/0.3	2598	12
2.5	36/0.3	4140	12
4.0	56/0.3	6045	8
6.0	84/0.3	8976	4

FIREX LSOH HALOGEN FREE FLAME RETARDANT 90 °C, CROSSLINKED



RR KABEL make single core unsheathed Multistrand High Conductivity plain annealed Copper, Cross linked Halogen Free Flame Retardant(HFFR) 90 °C Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 17048 (HSN Code: 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.00	14/0.3	2063	20
1.50	22/0.3	2904	12
2.50	36/0.3	4588	12
4.00	56/0.3	6732	8
6.00	84/0.3	9751	4

*FIREX LSOH – Insulation conforming to HFI XL 90 as per IS 17048

RR KABEL FR / FR-LSH / LSOH



RR KABEL make single core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC / FR-LSH PVC / Thermoplastic Halogen Free Flame Retardant (HFFR) 70 °C Insulated Industrial Cables in voltage grade upto and including 1100 Volts (HSN Code: 8544)

RATE / 200 MTR					
Size (Sq.mm)	Configuration	AMPS	RR KABEL FR FR PVC INSULATION As Per IS 694	RR KABEL FR-LSH FR-LSH PVC INSULATION As Per IS 694	RR KABEL LSOH Thermoplastic Halogen Free Flame Retardant (HFFR) 70 °C Insulation As Per IS 17048
0.75	24/0.2	8	2862	2961	3349
1.0	32/0.2	13	3737	3868	4222
1.5	30/0.25	17	5401	5589	5940
2.5	50/0.25	24	8797	9106	9586
4.0	56/0.3	30	13460	13931	14700
6.0	84/0.3	38	20013	20665	21802

*RR KABEL LSOH – Insulation conforming to HFI TP 70 as per IS 17048



COMMUNICATION CABLES

RR KĀBEL
WIRES & CABLES

- RATNA CO-X
- RATNA LAN
- RATNA COM
- CCTV CAMERA CABLE
- SPEAKER CABLE

RATNA CO-X



RR Kabel make Electrolytic grade solid annealed bare copper conductor gas injected physical polyethylene foam insulated, wrapped with Aluminium Mylar tape and Al alloy wire braided, Jelly flooded and PVC Jacketing in Black Colour, Co-Axial Industrial Cables. (HSN Code : 8544)

RG 59 F		RG 6 F		RG 11 F	
90 Mtr.	305 Mtr.	90 Mtr.	305 Mtr.	90 Mtr.	305 Mtr.
1955	6623	2498	8464	5565	18860

RATNA LAN



RR Kabel make Solid bare copper conductor 4 Pair unshielded twisted pair (UTP) Industrial cables for Computer Lan Network with Grey colour & FR PVC Jacket. (HSN Code : 8544)

CAT 5e		CAT 6	
100 Mtr.	305 Mtr.	100 Mtr.	305 Mtr.
3148	9599	4210	12839

RATNA COM



RR Kabel make Solid Electrolytic annealed bare copper conductor Industrial Switchboard & Telephone Cables with high density polyethylene insulation, paired, polyester taped, Nylon Rip Cord and Grey colour sheathed with FR PVC, generally conform to "ITD specification S/WS 113 C" (HSN Code : 8544). (Rate/90 Mtr Coil)

Dia	1 Pair	2 Pair	3 Pair	4 Pair	5 Pair	10 Pair	20 Pair
0.5 mm	896	1576	2325	3046	3795	7248	13762

CCTV CAMERA CABLES



RR Kabel make Annealed Tinned copper conductor, PE Insulated, ATC Braided, Polyester tape screened, PVC outer sheathed Industrial CCTV Camera Cables.(HSN CODE : 8544)

Size	Packing	Rate Per Coil	No. of Coils packed in an Outer Box
3 + 1	90 Mtr.	3682	3
4 + 1	90 Mtr.	4126	3

SPEAKER CABLES



RR Kabel make Multistrand Annealed bare copper conductor, PVC Insulated Industrial Speaker wires. (HSN CODE : 8544)

Size	Packing	Rate Per Coil	No. of Coils packed in an Outer Box
2C x 0.50	90 Mtr.	1794	10
2C x 0.75	90 Mtr.	2557	10
2C x 1.0	90 Mtr.	3226	8
2C x 1.5	90 Mtr.	4650	8
2C x 2.5	90 Mtr.	7409	8

* 3% Extra for Transparent sheath



INDUSTRIAL CABLES

RR KÄBEL
WIRES & CABLES

- FLEXIBLE SINGLE CORE CABLE
- FLEXIBLE MULTICORE CABLES
- SHIELDED CABLE
- BRAIDED CABLE

RR KABEL FR / FR-LSH / LSOH



RR KABEL make single core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC / FR-LSH PVC / Thermoplastic Halogen Free Flame Retardant (HFFR) 70 °C Insulated Industrial Cables in voltage grade upto and including 1100 Volts (HSN Code: 8544)

RATE / 100 MTR					
Size (Sq.mm)	Configuration	AMPS	RR KABEL FR FR PVC INSULATION As Per IS 694	RR KABEL FR-LSH FR-LSH PVC INSULATION As Per IS 694	RR KABEL LSOH Thermoplastic Halogen Free Flame Retardant (HFFR) 70 °C Insulation As Per IS 17048
10.0	140/0.3	52	17657	18274	19398
16.0	126/0.4	70	27951	28926	30553
25.0	196/0.4	88	45812	47645	51310
35.0	276/0.4	112	64082	66646	71772
50.0	396/0.4	146	91387	95042	102353
70.0	360/0.5	216	129511	134691	145053
95.0	480/0.5	262	174224	181192	195130
120.0	608/0.5	310	225431	234449	252483
150.0	750/0.5	355	279451	290630	312986
185.0	931/0.5	415	339865	353460	380649
240.0	1200/0.5	500	447122	465006	500776
300.0	1500/0.5	550	558189	580516	625170
400.0 *	2013/0.5	590	758501	788842	849522
500.0 *	2562/0.5	660	983197	1022525	1101180
630.0 *	3416/0.5	725	1306957	1359235	1463792

The item marked * are non stock items refer to marketing dept for delivery schedule MOQ packing etc.

*RR KABEL LSOH – Insulation conforming to HFI TP 70 as per IS 17048

RATNA FLEX SINGLE CORE



Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated Unsheathed Single core round flexible Industrial Power Cables for working voltages upto and including 1100 Volts (HSN CODE : 8544)

Size (Sq.mm)	Configuration	AMPS	Rate Per 100 Mtr
0.5	16/0.2	5	992
0.75	24/0.2	8	1408
1.0	32/0.2	13	1826
1.5	30/0.25	17	2627
2.5	50/0.25	24	4246
4.0	56/0.3	30	6692
6.0	84/0.3	38	9869

RATNA FLEX MULTICORE CABLES



Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated & PVC sheathed multicore round flexible Industrial Cables for working voltages upto and including 1100 Volts, as per IS 694 (HSN CODE : 8544)

Rate per 100 meter											
Size (Sq.mm)	CONFIG.	AMPS	2 CORE	3 CORE	4 CORE	Size (Sq.mm)	CONFIG.	AMPS	2 CORE	3 CORE	4 CORE
0.5	16/0.2	5	3081	4015	5012	25.0	196/0.4	88	103010	146034	192402
0.75	24/0.2	8	4008	5347	6811	35.0	276/0.4	112	-	203932	270243
1.0	32/0.2	13	4877	6605	8457	50.0	396/0.4	146	-	291112	379109
1.5	30/0.25	17	6534	9030	11759	70.0	360/0.5	216	-	409572	539937
2.5	50/0.25	24	10345	14413	18749	95.0	480/0.5	262	-	552503	724449
4.0	56/0.3	30	15811	22072	28913	120.0	608/0.5	310	-	697507	923778
6.0	84/0.3	38	22686	32359	42577	150.0	750/0.5	355	-	885391	1161275
10.0	140/0.3	52	40083	57431	74838	185.0	931/0.5	415	-	1087957	1412788
16.0	126/0.4	70	62621	88439	116531	240.0	1200/0.5	500	-	1413954	1910684
						300.0	1500/0.5	550	-	1763746	2386620

CONTROL CABLES



Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated & PVC sheathed multicore round flexible Industrial Control Cables (JZ-500), Voltages Grade 300/500 V. (HSN CODE : 8544)

Rate per 100 meter												
Size (Sq.mm)	CONFIG.	AMPS	5 CORE *	6 CORE *	7 CORE *	8 CORE *	10 CORE *	12 CORE *	14 CORE *	16 CORE *	19 CORE *	24 CORE *
0.5	16/0.2	5	6556	7610	8481	10070	12494	14674	16999	19068	22499	28799
0.75	24/0.2	8	8943	10701	11994	14382	17586	20918	24292	27710	33410	41849
1.0	32/0.2	13	11363	13319	15166	18064	22511	26457	30990	34744	42838	52721
1.5	30/0.25	17	15891	18866	21581	25310	31691	37406	43549	49053	58040	74365
2.5	50/0.25	24	25328	30708	35184	40800	51406	60539	71015	81173	96541	121193
4.0	56/0.3	30	39334	47887	55325	65155	81432	96463	112343	128042	151263	193260
6.0	84/0.3	38	58618	70933	82669	95636	122199	144848	167906	191239	225666	287932
10.0	140/0.3	52	100147	-	-	-	-	-	-	-	-	-
16.0	126/0.4	70	157808	-	-	-	-	-	-	-	-	-

Loading factor for Different Insulation / Sheath * -

FR Insulation	FR Sheath	FR-LSH / HR Insulation	FR-LSH / HR Sheath	LSOH Insulation	LSZH Sheath
5%	5%	10%	10%	35%	25%

The item marked * are non stock items, refer to marketing dept. for delivery schedule, MOQ, packing etc.

SUBMERSIBLE FLAT CABLES

RR Kabel makes 3 Core PVC Insulated and sheathed Industrial Flat cables for Submersible Motor, working voltages upto and including 1100 Volts, as per IS 694



Size (Sq.mm)	Configuration	Rate 100 mtr
1.5	22/0.3	9604
2.5	36/0.3	14974
4.0	56/0.3	21953
6.0	84/0.3	31834
10.0	140/0.3	55431
16.0	126/0.4	85967
25.0	196/0.4	135023

* For XLPE Insulated Submersible Flat Cables (Cu/XLPE/PVC), contact us for pricing and availability. MOQ will be applicable.

ONLY THE BEST SUBMERSIBLE CABLES CAN WITHSTAND THE HARSHTEST CONDITIONS.

- PVC & XLPE Insulation
- Electrolytic Grade
Annealed Copper
- Better Conductivity
- CE, REACH &
RoHS Compliant



AKALMAND BANO, SAHI CHUNO.

SHIELDED CABLES



Flexible / Stranded Bare Copper Conductor, PVC Insulated, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Shielded) Cables, Voltage Grade 300/500V, as per BS EN 50288-7

SIZE	Size in Sq.mm / Rate Per 100 Meter (in INR)					MOQ (KM)
	0.50	0.75	1.00	1.50	2.50	
2 Core	5355	6497	7566	9679	14233	3
3 Core	6703	8405	9988	12887	19782	3
4 Core	8382	10639	12775	16866	25511	3
5 Core	9634	12496	15174	20330	31683	3
6 Core	11259	14672	18058	23690	-	3
7 Core	12488	16477	20172	26970	41514	3
8 Core	14154	18759	22840	30899	49276	2
9 Core	15648	-	-	-	-	2
10 Core	17355	23076	28428	38999	61113	2
12 Core	20106	26980	33705	45557	72450	2
14 Core	22894	30614	38794	52660	84915	1
16 Core	25965	35560	43843	59697	96916	1
18 Core	28831	39228	48939	66719	109359	1
20 Core	31883	43018	54285	76409	121323	1
22 Core	35107	47483	59408	-	-	1
25 Core	39377	53442	67626	-	-	1
27 Core	42193	57367	71979	-	-	1

Note : Please contact to Technical Cell / HO for Technical Data Sheet.

SHIELDED ARMoured CABLES



Flexible / Stranded Bare Copper Conductor PVC / XLPE Insulated,
 Overall Aluminium Mylar Tape Shielded with ATC Drain Wire, PVC Inner Sheathed, GI Wire / Strip Armour And Outer PVC Sheathed
 Industrial Instrumentation (Shielded Armoured) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

SIZE	Size in Sq.mm / Rate Per 100 Meter (in INR)					MOQ (KM)
	0.50	0.75	1.00	1.50	2.50	
2 Core	10372	12030	13600	16323	21883	5
3 Core	12368	14517	16913	20255	28345	5
4 Core	14149	16950	19970	24315	35821	3
5 Core	16231	19795	23571	28815	42077	3
6 Core	18121	22428	26752	33889	-	3
7 Core	19367	24063	28637	37007	55488	3
8 Core	22046	27119	31994	41833	62251	3
9 Core	23574	-	-	-	-	3
10 Core	25321	31839	38977	51540	76583	3
12 Core	28628	36128	44473	58259	89920	3
14 Core	31745	40569	51713	67106	100250	3
16 Core	35483	47883	55865	75510	113288	3
18 Core	39997	49031	62452	83876	126040	3
20 Core	44832	54202	68427	95344	139588	2
22 Core	45833	59293	74130	-	-	2
24 Core	-	-	79633	-	-	2
25 Core	50192	65400	82118	-	-	2
27 Core	52747	69057	91126	-	-	2

Note : Please contact to Technical Cell / HO for Technical Data Sheet.

BRAIDED CABLES



Flexible / Stranded Bare Copper Conductor, PVC Insulated, Annealed Tinned Copper Braided with Optimum coverage and Outer PVC sheathed Industrial Braided cables, Voltage Grade 300/500V.

Size in Sq.mm / Rate Per 100 Meter (in INR)						
SIZE	0.25	0.50	0.75	1.00	1.50	2.50
2 Core	7072	8146	8842	10007	12763	18679
3 Core	7609	9087	10984	12643	16497	24526
4 Core	9149	11113	13608	16004	20638	31454
5 Core	11457	12980	16293	19077	25221	39121
6 Core	13498	14336	17238	21642	28320	-
7 Core	14252	15564	19873	23886	31961	49720
8 Core	15270	17554	22247	27203	36920	-
9 Core	-	-	-	-	41306	-
10 Core	18243	22301	28273	33687	45887	-
12 Core	20213	24256	32429	39414	53449	83149
14 Core	-	27786	37007	45595	62009	-
16 Core	-	31278	41721	51322	69819	-
18 Core	28449	34516	46762	57411	77993	-

Size in Sq.mm / Rate Per 100 Meter (in INR)				
SIZE	4.0	6.0	10.0	16.0
2 Core	26969	37164	-	-
3 Core	37022	51496	-	-
4 Core	46609	65672	110249	178354

Note : Minimum Order Quantity (MOQ)

Size - upto 0.25 x 8C - 5 KM, upto 0.25 x 8C to 18C and 0.50 to 1.50 x 7C - 3 KM,
 0.50 x 8C to 4.0 x 4C - 2 KM, 0.50 x 22C to 1.00 x 27C - 2 KM.

PAIR SHIELDED CABLES



Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Pair Shielded) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

Size in Sq.mm / Rate Per 100 Meter (in INR)							
Number of Pair	0.50	0.75	MOQ (KM)	1.00	1.50	2.50	MOQ (KM)
1	6482	7940	10	9836	11330	16304	5
2	10620	12907	5	16466	20456	30657	3
3	13744	17351	3	21877	28853	43604	3
4	15987	22314	3	28084	36703	56962	3
5	19483	27205	3	34815	44482	68134	3
6	22736	31955	3	41455	52709	80999	2
8	29188	41087	3	52074	69715	106633	2
10	35924	49912	3	64096	85336	132192	2
12	42746	59650	3	76081	101566	157697	2
14	-	-	-	-	116505	-	1
16	55519	78002	2	100799	135110	210443	1
20	68949	97249	2	124788	167681	261655	1
24	81794	115696	2	148703	200159	312794	1

Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Individual pair and Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Pair Shielded) Cables as per BS EN 50288-7.

Size in Sq.mm / Rate Per 100 Meter (in INR)							
Number of Pair	0.50	0.75	MOQ (KM)	1.00	1.50	2.50	MOQ (KM)
2	13781	16043	5	19651	24356	34741	2
3	17895	22259	5	27594	34036	49226	2
4	22850	27881	3	33527	44309	64433	2
5	26993	33824	3	42040	53780	78631	1
6	32073	40706	2	49289	63842	93571	1
8	42879	53113	2	65138	83909	123416	1
10	52693	65481	1	80460	103901	153182	1
12	62489	77811	1	95764	120346	182893	1
16	82500	100318	1	122572	160290	237263	1
20	102128	124387	1	153621	199282	295350	1
24	121739	148456	1	183483	238254	353417	1
25	-	-	-	190954	-	-	1

Note: The MOQ is given above, please send your requisition to Technical Cell / HO for Technical Data Sheet before finalizing the orders.

PAIR SHIELDED ARMOURED CABLES



Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire, PVC Inner Sheathed, GI Wire/Strip Armour and Outer PVC Sheathed Industrial Instrumentation (Overall Pair Shielded Armoured) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

Size in Sq.mm / Rate Per 100 Meter (in INR)							
Number of Pair	0.50	0.75	MOQ (KM)	1.00	1.50	2.50	MOQ (KM)
1	10473	12030	10	13730	16323	21883	5
2	16080	19125	5	22381	27332	38158	3
3	18859	22653	3	27106	35286	52630	3
4	22805	28068	3	33605	45552	63218	3
5	26073	33155	3	40442	51825	76357	3
6	29698	38132	3	49327	60485	89657	2
8	38827	47595	3	57968	78515	115955	2
10	42918	56629	3	70046	94635	142008	2
12	50142	66626	3	81974	111052	167856	2
14	-	-	-	-	126756	-	1
16	63286	85020	2	106337	145183	220902	1
20	77079	104304	2	129817	178638	272239	1
24	90098	122608	2	153091	210946	323314	1

Flexible / Stranded Bare Copper Conductor, PVC / XLPE Insulated, Twisted Pairs, Individual Pair and Overall Aluminium Mylar Tape Shielded with ATC Drain Wire, PVC Inner Sheathed, GI Wire / Strip Armour and Outer PVC Sheathed Industrial Instrumentation (Individual Pair and Overall Shielded Armoured) Cables, Voltage Grade 300/500V, as per BS EN 50288-7.

Size in Sq.mm / Rate Per 100 Meter (in INR)							
Number of Pair	0.50	0.75	MOQ (KM)	1.00	1.50	2.50	MOQ (KM)
2	18937	22136	5	25430	30506	40650	2
3	23661	27358	5	31852	39948	51759	2
4	28326	34070	3	40209	50337	66320	2
5	34335	42170	3	48954	57884	81772	1
6	39886	46432	2	54577	67818	96239	1
8	48044	59173	2	70587	87460	124924	1
10	57979	71743	1	85887	106912	153383	1
12	67818	84218	1	101073	126232	181690	1
16	87688	109548	1	130751	165725	239724	1
20	107103	134233	1	162142	204175	296187	1
24	126404	158824	1	192155	242492	352477	1
25	-	-	-	199644	-	-	1

Note: The MOQ is given above, please send your requisition to Technical Cell / HO for Technical Data Sheet before finalizing the orders.

TERMS & CONDITIONS:

GST : The above prices are exclusive of GST.

Packing : Order should be in Standard packing.

Freight : Value upto Rs. 2,00,000/- on 'TO-PAY' basis & above on 'PAID' basis

Note: This is Revised Price List, hence all previous Price List & Discount will not be considered.

**As per the international practice which is also adopted by BIS, for all cables with ISI mark the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guidelines and are as per market convention, it may vary within the prescribed limit of IS 8130, with related classes and tables

THE PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.



WORLD OF EXCELLENCE



As a USD 850 + million conglomerate, we are one of the largest, diversified & most prominent brands in the Indian electrical industry, with a noteworthy presence in over 85+ countries across the world. We offer a multi faceted range of quality products through our 10 successfully operating companies, 42 marketing offices and 12 manufacturing facilities.

At RR Global, we continue to innovate to ensure only the finest products reach our customers.



Ram Ratna House, Oasis Complex, P. B. Marg, Worli, Mumbai - 400 013.

T: +91 - 22 - 2494 9009 / 2492 4144 • **F:** +91 - 22 - 2491 2586 • **E:** mumbai.rrkabel@rrglobal.com

305/A, Windsor Plaza, R. C. Dutt Road, Alkapuri, Vadodara - 390 007.

T: +91 - 265 - 2321 891 / 2 / 3 • **F:** +91 - 265 - 2321 894 • **E:** vadodara.rrkabel@rrglobal.com

R R KABEL LIMITED

Regd. Office : Ram Ratna House, Oasis Complex, P. B. Marg, Worli, Mumbai - 400 013.

Ahmedabad: 079 - 4900 0100, **Bengaluru:** 080 - 4125 0079 / 4090 2221, **Bhubaneswar:** 0674 - 2971 231,
Chennai: 044 - 2829 2329 / 2429, **Coimbatore:** 0422 - 2910 560, **Guwahati:** 0361 - 2730772,
Haryana: 0130 - 2986 986, **Indore:** 0731 - 4009 863, **Jaipur:** 0141 - 2741417, **Jalandhar:** 0181 - 500 3394,
Ernakulam: 0484 - 2378 782, **Kolkata:** 033 - 6607 1233 / 2262 8660, **Lucknow:** 0522 - 4113 745 / 46,
Madurai: 0452 - 4370 340, **New Delhi:** 011 - 4303 8395 / 2735 5477 / 78, **Pune:** 8956 811 100,
Raipur: 0771 - 2971 518, **Rajkot:** 0932 7722 501, **Secunderabad:** 040 - 2780 4098,
Silvassa: 0260 - 2641 333, **Surat:** 9376 507 543, **Trichy:** 8939 830 338.

www.rrkabel.com • www.rrglobal.com

The technical data mentioned in the book has been derived to have the best production place. Having known that innovation has always been the base for R R Kabel products, the technical data would vary from time to time. Hence, current details should always be checked with R R Kabel for accuracy.

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
RoHS = Restriction of Hazardous Substances | **CE** = Conformance Européenne
ISI = Indian Standard Institution